






BD-RS 2462

Fût octo-conique, renforcé, en acier,
62 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.
*Reinforced octagonal conical steel pole,
62 mm at top, 2 rows of threaded holes at 100 and 200 mm from top.*

								
8	62 x 190	600 x 130	500	110 x 124	300	20/18 x 400	139	
9	62 x 190	600 x 130	500	110 x 126	300	20/18 x 400	152	
10	62 x 190	600 x 130	500	110 x 128	300	20/18 x 400	165	
11	62 x 190	600 x 130	500	110 x 129	300	20/18 x 400	178	
12	62 x 190	600 x 130	500	110 x 130	300	20/18 x 400	191	

		24m/s		26ms		28m/s		30m/s		34m/s		M	T	
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
8	50	1,86	1,49	1,54	1,22	1,27	1	1,06	0,83	0,75	0,56	2125	402	0,6 x 1,2
9	50	1,44	1,15	1,17	0,9	0,94	0,72	0,77	0,57	0,49	0,35	2150	399	0,6 x 1,2
10	50	1,11	0,85	0,87	0,65	0,67	0,49	0,53	0,36	0,3	0,17	2169	403	0,6 x 1,2
11	50	0,82	0,61	0,61	0,43	0,45	0,3	0,32	0,19	0,13		2188	412	0,6 x 1,2
12	50	0,59	0,4	0,41	0,25	0,27	0,13	0,16				2180	371	0,6 x 1,2