










BE 2103

Fût octo-conique en acier,
103 mm sur plats en tête, 2 rangées de crevés taraudés à 100 et 450 mm du sommet.
*Octagonal conical steel pole,
At top 103 mm across flats, 2 rows of threaded holes at 100 and 450 mm from top.*




							
5	103 x 193	600 x 130	500	110 x 119	300	20/18 x 400	92
6	103 x 193	600 x 130	500	110 x 122	300	20/18 x 400	107
7	103 x 193	600 x 130	500	110 x 125	300	20/18 x 400	123

			24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
			Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
5	50	3,08	2,44	2,54	2,05	2,17	1,71	1,86	1,47	1,37	1,07	1499	380	0.5 x 1.1	
6	50	2,22	1,76	1,83	1,44	1,51	1,2	1,27	0,99	0,9	0,68	1502	351	0.5 x 1.1	
7	50	1,61	1,25	1,29	1	1,06	0,81	0,87	0,65	0,58	0,41	1527	341	0.5 x 1.1	

BE-RS 2103

Fût octo-conique, renforcé, en acier,
103 mm sur plats en tête, 2 rangées de crevés taraudés à 100 et 450 mm du sommet.
*Reinforced octagonal conical steel pole,
At top 103 mm across flats, 2 rows of threaded holes at 100 and 450 mm from top.*

							
7	103 x 193	600 x 130	500	110 x 122	300	20/18 x 400	142
8	103 x 193	600 x 130	500	110 x 125	300	20/18 x 400	158
9	103 x 193	600 x 130	500	110 x 128	300	20/18 x 400	173

			24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
			Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
7	100	2,44	1,98	2,03	1,61	1,69	1,32	1,42	1,1	1	0,76	2241	447	0.6 x 1.2	
8	100	1,83	1,44	1,49	1,16	1,21	0,93	0,99	0,75	0,66	0,48	2274	437	0.6 x 1.2	
9	100	1,37	1,05	1,07	0,81	0,84	0,62	0,66	0,46	0,39	0,24	2285	435	0.6 x 1.2	