













OLERON 2462

Fût rond-conique en acier,
62 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.
*Round conical steel pole,
62 mm at top, 2 rows of threaded holes at 100 and 200 mm from top.*

								
8	62 x 200	500 x 104	500	120 x 130	300	20/18 x 400	129	
9	62 x 219	600 x 134	500	120 x 150	300	20/18 x 400	150	
10	62 x 237	600 x 137	500	120 x 170	300	20/18 x 400	173	
12	62 x 269	600 x 140	500	145 x 195	300	25/24 x 600	227	

		24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
8	100	1,49	1,22	1,25	1,01	1,05	0,85	0,89	0,73	0,67	0,54	1807	290	0.5 x 1.2
9	100	1,21	0,98	1	0,81	0,83	0,67	0,71	0,57	0,52	0,42	1851	288	0.5 x 1.2
10	100	1,27	1,04	1,05	0,85	0,88	0,71	0,73	0,6	0,54	0,42	2247	326	0.6 x 1.2
12	100	1,29	1,07	1,07	0,87	0,89	0,71	0,73	0,59	0,52	0,4	3080	401	0.7 x 1.4