














OMEGA 2376






Fût rond-conique en acier,
76 mm en tête, 2 rangées de crevés taraudés.
Round conical steel pole,
76 mm at top, 2 rows of threaded holes at 100 and 200 mm from top.




								
4	76 x 132	500 x 74	500	70 x 75	200	16/14 x 300	37	
5	76 x 146	450 x 76	500	72 x 90	200	16/14 x 300	47	

			24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
			Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
4	50		1,51	1,21	1,27	1	1,09	0,85	0,93	0,73	0,71	0,56	596	174	0,4 x 0,7
5	50		1,32	1,05	1,1	0,88	0,93	0,75	0,79	0,64	0,6	0,48	747	181	0,4 x 0,8

OMEGA 2478

Fût rond-conique en acier,
78 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.
Round conical steel pole at 100 and 200 mm from top,
78 mm at top, 2 rows of threaded holes at 100 and 200 mm from top.

								
6	78 x 156	500 x 76	500	98 x 89	300	20/18 x 400	84	
7	78 x 169	500 x 101	500	98 x 98	300	20/18 x 400	99	
8	78 x 182	500 x 103	500	100 x 115	300	20/18 x 400	118	
9	78 x 195	500 x 104	500	100 x 129	300	20/18 x 400	136	
10	78 x 207,7	500 x 105	500	103 x 142	300	20/18 x 400	156	

			24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
			Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
6	50		1,34	1,07	1,11	0,89	0,94	0,75	0,81	0,65	0,6	0,49	983	202	0,6 x 0,8
7	50		1,27	1,03	1,06	0,85	0,89	0,72	0,76	0,61	0,57	0,46	1216	221	0,5 x 0,9
8	50		1,22	1	1,01	0,83	0,85	0,7	0,73	0,6	0,55	0,45	1471	243	0,5 x 1,1
9	50		1,07	0,87	0,88	0,72	0,73	0,6	0,62	0,51	0,46	0,36	1593	250	0,5 x 1,1
10	50		0,83	0,67	0,67	0,55	0,56	0,45	0,46	0,37	0,32	0,25	1596	249	0,5 x 1,1