












STEPAC

Fût tubulaire rétreint, en acier,
89 mm en tête, une lumière pour embouts démontables.
*Tubular stepped steel pole,
89 mm at top, one slotted hole for removable spigots.*

							
3,5	89 x 140	400 x 85	500	80 x 100	200	16/14 x300	36,5
4	89 x 140	400 x 85	500	80 x 100	200	16/14 x300	40
4,5	89 x 140	400 x 85	500	80 x 100	200	16/14 x300	43,5
5	89 x 140	400 x 85	500	80 x 100	200	16/14 x300	47

		24m/s		26m/s		28m/s		30m/s		34m/s		M m.daN	T daN	 L x H
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I			
3,5	50	1,93	1,56	1,61	1,32	1,39	1,14	1,2	0,99	0,92	0,76	615	197	0,4 x 0,7
4	50	1,47	1,16	1,22	0,98	1,05	0,83	0,9	0,71	0,68	0,54	584	172	0,4 x 0,7
4,5	50	1,11	0,88	0,93	0,73	0,78	0,61	0,67	0,53	0,5	0,4	567	157	0,4 x 0,7
5	50	0,84	0,66	0,7	0,55	0,59	0,46	0,49	0,39	0,37	0,29	556	147	0,5 x 0,6